


Operative Office: Via Pietro Nenni 79/E,
10036 Settimo Torinese (TO) – ITALY
Tel +39 011.0378820 – +39 011.0378821 – Fax +39
011.19835584

Registered Office: Corso Giacomo Matteotti 36, 10121
Torino (TO) ITALY



ROPE 40- Technical Details

DETECTOR	
Product code	ROPE40F-AXv2
Dimensions with centring system	46x28x12 cm
Weight	20 kg
Material	Iron – Aluminium - Polyurethane
Type of Magnet	NdFeB
Maximum rope diameter	40 mm
Number of ropes checked at the same time	1

Sensors		
LF sensors	Max rope diameter	40 mm
	Suggested Min rope diameter	30 mm

Sensitivity of Sensors	As defined by EN 12927-8
Suggested Speed Range	0.1 – 2 m/s
IP→ measuring head	65
IP→ acquisition system	53
	Optional protection up to IP 69 on request

IASH ACQUISITION SYSTEM	
Sampling frequency for channel	up to 5 kS/s
Indicative IASH battery life in continuous operation	10 hours
Battery charging	230 Vac - 50 Hz

OTHER CHARACTERISTICS	
Operating temperature	-20 °C + 50 °C
Working Environment	ATEX certification on request
Transport accessories	Professional suitcases